



MODEL 149

The ultra-handly splicer for synthetics up to 7000 tex.

Airbond already leads the world in splicers for the glass and carbon fibre business, with its pioneering 113,114 and 701 models. Now the company's latest patented technology is set to transform the business. The 149 simplifies the splicing action even further, permitting a design which can be used in the smallest spaces. The 149 is as effective and versatile as our old ones, joining a huge range of counts in modern fibres. It's lighter and handier than anything Airbond has made before. And as with the 701, the working parts are protected from the wear and tear, safe inside an impact-resistant shell.

The 149 represents a leap forward in design, matching or out-performing all others in one simple, elegant package. Strengths of 90 per cent of the parent yarns are easily attainable, in a remarkably widest range of counts, considering the size of the splicer. And, like other splicers in the Airbond range, the 149 is rugged, reliable and simple to maintain.

Splice format: Ends opposed.
 Applications: Composites processes such as filament winding, pultrusion and weaving
 Yarns: Carbon fibre, glass fibre, aramid, Panox, synthetic C.F.
 Yarn counts: Up to 7000 tex.
 Twist: Zero or low twist

Airbond, Unit 1, Pavilion Industrial Estate
 Pontypool, NP4 6NF, UK
 +44 1495 755661
enquiries@airbondsplicer.com



airbond

An ISO 9001:2015 company
 An ISO 14001:2015 company

Outil pour épissage des fibres lourdes pour des applications industrielles. Disponible dans de nombreux formats.

Forme d'épissure "extrémités opposées"

Simple, solide et facile à réparer.

Disponible avec contrôle de débit.

Bon pour la plupart des processus composites.

Werkzeug zum Spleißen schwerer Fasern für industrielle Anwendungen. In vielen Formaten erhältlich.

Spleißform "Enden entgegengesetzt"

Einfach, stark und leicht zu reparieren.

Erhältlich mit Durchflussregelung.

Gut für die meisten Verbundprozesse.

Gut für alle Kunststoffe einschließlich Kohlenstoff und Glas. Bis zu ca. 7000 tex

Strumento che unisce di fibre pesanti per applicazioni industriali. Disponibile in molti formati

Metodo di giunzione "Fine opposto"

Semplice, resistente e facile da riparare.

Disponibile con controllo di flusso. Disponibile con timer di durata.

Buono per la maggior parte dei processi compositi.

Buono per tutti i sintetici tra cui carbonio e vetro. Fino a circa 7000 tex

Herramienta para empalme de fibras pesadas para aplicaciones industriales. Disponible en muchos formatos.

Forma de empalme "extremos opuestos"

Simple, fuerte y fácil de reparar.

Disponible con control de flujo.

Bueno para la mayoría de los procesos composites modernos

Bueno para todos los sintéticos, incluidos el carbono y el vidrio. Hasta aproximadamente 7000 tex

産業用用途向けの重繊維のスプライシング用ツール。

スプライスフォーム「両端反対」

シンプルで丈夫で、修理も簡単。

フロー制御で利用できます。

最新の複合材プロセスに最適です。

カーボンやガラスを含むすべての合成繊維に適しています。最大約7000 tex

用于工业应用拼接重纤维的工具。

拼接形式“两端相反”

简单·坚固且易于维修。

可以提供流量控制。

适用于大多数现代复合材料工艺。

适用于所有合成纤维·包括碳和玻璃·高达约7000 tex



An ISO 9001:2015 company

An ISO 14001:2015 company

An ISO 14001:2015 company